

## 2601 – GRECATO Super Flexible Corrugated Radiator Hose



This is an EPDM flexible radiator hose, designed for vehicle radiator hoses and hot water applications.

The hose has a smooth EPDM black rubber tubing and has a textile braid and steel wire helix reinforcement.

### Technical Specifications

<b>Tube</b>	Smooth EPDM black rubber. Antifreeze and ozone resistant
<b>Cover</b>	Ozone resistant corrugated
<b>Reinforcement</b>	Steel wire helix & textile braid.
<b>Temperature Range</b>	-40°C to +125°C
<b>Safety Factor</b>	3 x Working pressure
<b>Application</b>	Vehicle radiator hose, hot water

### Product Table

ID		OD	Working Pressure	Burst Pressure	Vacuum	Bend Radius	Weight	Max Coil
mm	inch	mm	bar	bar	M.H2O	mm	kg/m	Metres
19	3/4"	28	10	30	-0.920	114	0.385	40
22	7/8"	30	10	30	-0.920	132	0.437	40
25	1"	34	10	30	-0.920	153	0.495	40
28	1 1/8"	36	10	30	-0.920	168	0.527	40
32	1 1/4"	41	10	30	-0.920	192	0.665	40
35	1 3/8"	45	10	30	-0.920	210	0.790	40
38	1 1/2"	47	10	30	-0.920	228	0.777	40
45	1 3/4"	55	10	30	-0.920	270	1.146	40
51	2"	61	10	30	-0.920	305	1.535	40