

9042 – Diesel Fuel & Oil 10 Bar Delivery Hose



General purpose fuel & oil delivery, also fuel filler hose with a black synthetic elastomer rubber tube and abrasion, ozone & hydrocarbon resistant cover.

Technical Specifications

Tube	6-25mm ID: Synthetic elastomer rubber, 32-76mm ID: Conductive NBR rubber.
Cover	Black conductive CR - abrasion, ozone & hydrocarbon resistant
Reinforcement	High tensile textile cords
Temperature Range	-10°C up to +70°C
Safety Factor	3 x Working pressure.
Application	General purpose diesel & oil delivery hose

Product Table

ID		OD	Working Pressure	Burst Pressure	Bend Radius	Weight	Max Coil
mm	inch	mm	bar	bar	mm	kg/m	Metres
6	1/4"	13	10	30	48	0.14	100
8	5/16"	15	10	30	64	0.17	100
10	3/8"	17	10	30	80	0.20	100
13	1/2"	20	10	30	104	0.25	100
16	5/8"	27	10	30	160	0.44	10
19	3/4"	27	10	30	152	0.40	100
22	7/8"	33	10	30	220	0.60	100
25	1"	35	10	30	200	0.63	100
32	1 1/4"	44	10	30	128	0.59	61
38	1 1/2"	50	10	30	152	0.69	61
51	2"	63	10	30	204	0.91	61
76	3"	92	16	48	350	2.43	30