

2586 – Light Duty PVC Water Delivery & Suction Hose



This is a light duty green transparent PVC suction and delivery hose. It is suitable for suction and delivery of water, slurry, and light chemicals in agricultural, industrial and construction applications.

The tube has a green tinted PVC construction and contains a white shock resistant rigid PVC spiral reinforcement. The tubing is abrasion and ozone resistant.

We also offer Cam & Groove and Bauer style fittings.

Technical Specifications

Tube	Green tint transparent PVC - abrasion & ozone resistant. Smooth bore.
Cover	Clear PVC
Reinforcement	White shock resistant rigid PVC
Temperature Range	-10°C to +55°C
Safety Factor	3 x Working pressure
Application	Light duty Suction & Delivery of water & liquids.

Product Table

ID		OD	Working Pressure	Burst Pressure	Vacuum	Bend Radius	Weight	Max Coil
mm	inch	mm	bar	bar	M.H2O	mm	kg/m	Metres
12	1/2"	17	10	30	7	50	0.17	30
16	5/8"	22	9	27	7	64	0.2	30
19	3/4"	25	7	21	7	110	0.28	50
25	1"	29	7	21	7	138	0.39	50
32	1 1/4"	37	6	18	7	176	0.47	50
38	1 1/2"	43	5	15	7	209	0.56	50
51	2"	56	5	15	7	281	0.82	50
63	2 1/2"	69	7	21	7	290	1.07	30
76	3"	86	7	21	7	304	1.36	30