

3652 – Wyreflex Neoprene Fabric Ducting – 4 Metres



This is a double ply neoprene coated tubing lined with EPDM which offers excellent flexibility, reinforced with a twin steel wire helix.

Suitable for suction and conveyance of air, fumes and gases, dust collection and light materials handling.

Technical Specifications

Tube	Double ply neoprene coated polyester fabric. Excellent flexibility.
Cover	Black with yellow stripe
Reinforcement	Twin wire helix
Temperature Range	-55°C to +130°C
Application	Suction & conveyance of air, fumes, dust & light material handling.

Product Table

ID		Working Pressure	Vacuum	Bend Radius	Weight	Max Coil
mm	inch	bar	M.H2O	mm	kg/m	Metres
32	1 1/4"	0.7	0.3	45	0.4	4
38	1 1/2"	0.7	0.3	45	0.4	4
44		0.65	0.3	60	0.4	4
51	2"	0.65	0.3	60	0.5	4
63	2 1/2"	0.6	0.25	70	0.7	4
70		0.6	0.25	95	0.7	4
76	3"	0.6	0.2	95	0.7	4
82		0.5	0.2	110	0.9	4
102	4"	0.5	0.15	120	1.3	4
127	5"	0.5	0.1	145	1.7	4
152	6"	0.5	0.1	175	2.1	4
165	6 1/2"	0.45	0.05	200	2.5	4
203	8"	0.3	0.05	240	3.2	4