

## TDR2000

### TYRE INFLATOR

The Jamec Pem TDR 2000 Tyre Inflator represents quality and guaranteed accuracy. The classic hand held, slimline design is easy to hold. Designed to last in rugged workshop environments and utilised in a majority of Australian service stations.



guaranteed  
precision

Designed to meet EN standards and constructed in die cast aluminium for lightweight ease of use. Dual scale standard calibration is 0 - 138 p.s.i and 0 - 9.6 bar.

Wire sheathed hose eliminates kinking. Ergonomically designed two stage trigger.

Magnified linear scale is to a guaranteed accuracy. Each gauge is supplied complete with a certificate of calibration and full installation operation and service instructions. Packaged in a robust, easy to display colour box. Manufactured to the highest quality standards.

- Die cast aluminium body with steel operating lever and impact absorbing bumper
- Supplied with official calibration certificate
- Stamped serial number for individual I.D.
- Colour co-ordinated bumper and face plate
- Designed in Australia
- Ideal for service station forecourts
- Wire sheathed hose eliminates kinking
- Rubber grip on chuck
- ROHS compliant



**AUSTRALIA'S  
NO.1 TYRE  
INFLATOR**



CE COMPLIES WITH  
EN12645: 2014\*

Part No.	10.2000
Description	Hand held TDR
Type of Inflator	Analogue, Linear
Reader unit	Linear with magnifying glass
Chuck type	Hold on
Chuck style	Dual angle
Max. inflation	138 p.s.i
Scale	0-138 p.s.i / 0-960 kPa
Inlet size	1/4 " BSP female
Hose length	500 mm
Dimensions	265 L x 50 W x 70 H mm
Weight	0.95 kg
Accuracy*	± 2 p.s.i @ 25-75 p.s.i
Operation	Inflate, deflate, measure
Supply pressure max.	200 p.s.i
Powered by	N/A
Battery life (continuous use)	N/A
Inflation volume	500 L/min @ 188 p.s.i