

Smoothbore Ducting – Airduct 350



SKU	350
REF	4574
Tube	0.7mm Clear smooth bore Food Grade polyurethane tube
Cover	
Reinforcement	Copper coated steel wire helix within wall, antistatic.
Application	Suction and transport of abrasive materials, vapours, food products, powders, granulates, seeds, grain, etc.
Temp Range	-40°C to + 90°C (Intermittent to +125°C)
Conforms to	FDA21 CFR 177.2600 & 178.2010
Safety factor	

ID		OD	Working Pressure	Vacuum	Radius	Weight	Max Coil
mm	inch	mm	bar	BAR	mm	kg/m	Metres
38	1 1/2"	45	1.78	0.525	31	0.31	10
50	2"	57	1.35	0.435	38	0.4	10
65	2 1/2"	70	1.02	0.295	47	0.52	10
75	3"	82	0.91	0.22	50	0.59	10
100	4"	107	0.69	0.115	68	0.8	10
125	5"	132	0.55	0.08	83	0.98	10
150	6"	157	0.455	0.075	98	1.4	10
160	6 1/2"	167	0.415	0.065	104	1.5	10
175	7"	182	0.355	0.05	113	1.63	10
200	8"	207	0.315	0.05	128	1.86	10
225	9"	232	0.265	0.035	143	2.08	10
250	10"	257	0.24	0.02	158	2.31	10
300	12"	307	0.2	0.02	188	2.77	10