

PRO X 30M WITH EXTREME ULTRAFLEX HOSE - WATER

PRO:X
HELIX ULTRA-COIL™

**Built for extreme temperatures!
Won't bend or kink!**

Part No.	58.3045OS
Hose length	30 m
Hose I.D.	11.5 mm, 1/2 "
Hose O.D.	15.8 mm, 5/8 "
Hose material	Blended rubber & PVC
Leader hose length	2 m with 1/4 " BSP male fitting
Reel/Case type	Retractable / polypropylene
Auto lock/auto rewind	Yes
Max. working pressure	150 p.s.i
Fitting size	1/4 " BSP male brass swivel
Bracket	180° pivoting
Weight	10.5 kg
Application	Water

**Also available
with 20m Hose!**

Part No. 58.3034OS



EXTREME
ULTRAFLEX
REINFORCED HOSE

PRO X 30M WITH EXTREME ULTRAFLEX HOSE - AIR

PRO:X
HELIX ULTRA-COIL™

**Built for extreme temperatures!
Won't bend or kink!**

Part No.	58.3023OS
Hose length	30 m
Hose I.D.	9.2 mm, 3/8 "
Hose O.D.	15.2 mm
Hose material	Blended rubber & PVC
Leader hose length	2 m with 1/4 " BSP male fitting
Reel/Case type	Retractable / polypropylene
Auto lock/auto rewind	Yes
Max. working pressure	300 p.s.i, 2068 kPa
Fitting size	1/4 " BSP male brass swivel
Bracket	180° pivoting
Weight	10.5 kg
Application	Air

**Also available
with 20m Hose!**

Part No. 58.3012OS



EXTREME
ULTRAFLEX
REINFORCED HOSE