

Anti-static Unleaded Fuel, Diesel, Oil Suction & Delivery Hose



SKU	ASO
REF	4481
Tube	Smooth black fuel resistant nitrile rubber
Cover	Wrapped black CR/ NBR rubber.
Reinforcement	Polyester cord and steel wire helix.
Application	Suction & delivery of oils & fuels up to 40% aromatic content. Also use for hydraulic return lines.
Temp Range	-30°C to +80°C
Conforms to	SAE 100 R4 J517 + BS 3492
Safety factor	4 x Working Pressure

ID	OD	Working Pressure		Bend Radius	Weight	Max Coil
		bar	psi			
mm	mm			mm	kg/mtr	metres
19	32	21	315	100	0.6	60
	36	10	150	120	0.73	60
25	38	17	250	125	0.85	60
32	44	14	200	160	1	60
35	45	10	150	170	1.03	60
38	51	10	150	190	1.2	60
45	54	10	150	225	1.3	60
48	60	10	150	240	1.33	60
51	65	10	150	255	1.35	60
57	69	10	150	285	1.6	60
60	71	10	150	360	1.75	60
63	77	10	150	380	1.95	60
70	84	10	150	415	3	60
76	93	10	150	455	3.5	60
90	102	10	150	500	4.55	60
102	118	10	150	610	4.85	60
114	132	10	150	640	5.8	40
127	145	10	150	700	6.25	40
152	171	10	150	1000	8	30