

## 2575 – Standard Duty 20 Bar Rubber Compressed Air & Water Hose



This is a standard duty 20 bar rubber air and water hose, suitable for many compressed air, water and general industrial applications.

The tube is a black synthetic elastomer reinforced by high tensile textile cords and is protected by a smooth black synthetic elastomer with excellent abrasion, ozone and oil mist resistance.

### Technical Specifications

<b>Tube</b>	Black synthetic elastomer, silicone free.
<b>Cover</b>	Smooth black synthetic elastomer. Oil mist, abrasion and ozone resistant.
<b>Reinforcement</b>	High tensile textile cords
<b>Temperature Range</b>	-10°C to +60°C
<b>Safety Factor</b>	3 x working pressure
<b>Application</b>	Compressed air and water delivery

### Product Table

ID		OD	Working Pressure	Burst Pressure	Bend Radius	Weight	Max Coil
mm	inch	mm	bar	bar	mm	kg/m	Metres
6	1/4"	13	20	60	48	0.15	100
8	5/16"	15	20	60	64	0.18	100
10	3/8"	17	20	60	80	0.24	100
13	1/2"	21	20	60	104	0.30	100
16	5/8"	25	20	60	128	0.40	100
19	3/4"	29	20	60	152	0.47	100
25	1"	36	20	60	200	0.64	100