

## Light Duty PVC Water Delivery & Suction Hose



<b>SKU</b>	S264
<b>REF</b>	2586
<b>Tube</b>	Green tint transparent PVC - abrasion & ozone resistant. Smooth bore.
<b>Cover</b>	Clear PVC
<b>Reinforcement</b>	White shock resistant rigid PVC.
<b>Application</b>	Light duty Suction & Delivery of water & liquids.
<b>Temp Range</b>	-10°C to +55°C
<b>Conforms to</b>	
<b>Safety factor</b>	3 x Working pressure

ID		OD	Working Pressure	Breaking Pressure	Vacuum	Bend Radius	Weight	Max Coil
mm	inch	mm	bar	bar	M.H2O	mm	kg/m	Metres
12	1/2"	17	10	30	7	50	0.17	30
16	5/8"	22	9	27	7	64	0.2	30
19	3/4"	25	7	21	7	110	0.28	50
25	1"	29	7	21	7	138	0.39	50
32	1 1/4"	37	6	18	7	176	0.47	50
38	1 1/2"	43	5	15	7	209	0.56	50
51	2"	56	5	15	7	281	0.82	50
63	2 1/2"	69	7	21	7	290	1.07	30
76	3"	86	7	21	7	304	1.36	30