

9016 – Light Duty VULCANO PU ZR Polyurethane Extract Ducting



This is a light duty polyurethane ducting. It has a 0.4mm clear corrugated polyurethane tube and is reinforced with a copper coated steel anti-static wire helix embedded in the wall.

This ducting is designed for more lightweight applications such as dust, woodworking, and air extraction, and offers a high degree of flexibility.

Technical Specifications

Tube	0.4 mm Clear corrugated polyurethane tube
Reinforcement	Copper coated steel wire helix within wall, antistatic.
Temperature Range	-40°C to + 90°C (Intermittent to +125°C)
Application	Woodworking, dust, air extraction, etc

Product Table

ID	OD	Pressure	Vacuum	Weight	Max Coil
mm	inch	bar	M.H2O	kg/m	Metres
38	1 1/2"	0.61	0.29	0.22	10
50	2"	0.49	0.26	0.28	10
60		0.41	0.21	0.34	10
65	2 1/2"	0.38	0.18	0.36	10
80	3"	0.31	0.13	0.44	10
90	3 1/2"	0.29	0.11	0.49	10
100	4"	0.25	0.09	0.51	10
115	4 1/2"	0.22	0.08	0.58	10
120		0.21	0.06	0.61	10
125	5"	0.20	0.06	0.63	10
140	5 1/2"	0.18	0.06	0.71	10
150	6"	0.17	0.05	0.76	10
160		0.16	0.04	0.81	10
180	7"	0.14	0.04	0.90	10
200	8"	0.12	0.03	1.03	10
225	9"	0.11	0.02	1.16	10